

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) &amp; 453/2010

## 1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1 Product identifier

Product Name

**UNIPOL ECOFREPS**

Chemical Name

Expandable Polystyrene (self extinguishing).  
Expandable Polystyrene (containing pentane as  
expanding agent).

Synonyms

EPS-FR, Flame Retardent Expandable polystyrene,  
poly(phenylethene).

Trade name

**UNIPOL ECOFREPS**

CAS No.

None assigned.

EINECS No.

None assigned.

REACH Registration No.

None assigned.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use(s)

Used primarily for the manufacture of foamed thermal  
insulation and packaging.

Uses advised against

None known.

### 1.3 Details of the supplier of the Safety Data Sheet

#### 1.3.1 EU Representative

Telephone

Unipol Holland BV  
Postbox 824  
5340 AV Oss  
Netherlands

E-mail

+ 31 412 643 243

E-mail (competent person)

algemeen@unipol.nl

Technical contact:

a.janssen@unipol.nl

algemeen@unipol.nl

### 1.4 Emergency telephone number

Emergency Phone No.

+ 31 412 643 243

Dutch National Poison Information Centre:

+ 31 (0)30 - 274 88 88

(only for professional emergency aid personell, in case of  
calamities)

## 2. SECTION 2: HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

#### 2.1.2 Regulation (EC) No. 1272/2008 (CLP)

-

### 2.2 Label elements

#### 2.2.2 Label elements

According to Regulation (EC) No. 1272/2008 (CLP).

Product Name

**UNIPOL ECOFREPS**

Hazard Pictogram

None.

Signal word(s)

None.

Hazard statement(s)	EUH018: In use may form flammable/explosive vapour-air mixture.
Precautionary statement(s)	EUH210: Safety data sheet available on request. P210: Keep away from heat, sparks, open flame, hot surfaces - No smoking. P233: Keep container tightly closed. P243: Take precautionary measures against static discharge. P403 + P235: Store in a well-ventilated place. Keep cool.
<b>2.3 Other hazards</b>	Product releases pentane, a flammable hydrocarbon.
<b>2.4 Additional Information</b>	May cause irritation to skin and eyes. For full text of H/P phrases see section 16.

### 3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Polystyrene (CAS No. 9003-53-6), containing pentane isomers as blowing agent and brominised polymer as flame retardant.

#### 3.1 Polymer

EC Classification No. 1272/2008

Hazardous ingredient(s)	%W/W	CAS No.	EC No.	REACH Registration No.	Hazard pictogram(s) and Hazard statement(s)
Pentane (mixed isomers)	<7	109-66-0 78-78-4	203-692-4 201-142-8	01-2119459286-30 01-2119475602-38	GHS02, Flam. Liq. 1; H224, GHS08, Asp. Tox. 1; H304, GHS07, STOT SE 3; H336, GHS09, Aquatic Chronic 2; H411, EUH066.

For full text of H/P phrases see section 16.

#### 3.2 Additional Information

Contains < 1 % polymerized bromide. A non-hazardous ingredient according Directives (EC) Nr. 1272/2008 and 67/548/EEC en 1999/45/EC.

See Section: 15.1.1.

### 4. SECTION 4: FIRST AID MEASURES



#### 4.1 Description of first aid measures

Inhalation	Remove persons affected by vapour to fresh air. If symptoms persist, obtain medical attention.
Skin Contact	Wash skin with soap and water. If symptoms persist, obtain medical attention.
Eye Contact	Irrigate with eyewash solution or clean water, holding the eyelids apart, for at least 15 minutes. If symptoms persist, obtain medical attention.
Ingestion	Unlikely to be hazardous if swallowed. IF SWALLOWED: Do not induce vomiting. Obtain medical attention immediately if ingested.

- |   |  |
|---|--|
| <b>4.2 Most important symptoms and effects, both acute and delayed</b>            | Inhalation: headache, dizziness.   |
| <b>4.3 Indication of immediate medical attention and special treatment needed</b> | Eyes and skin contact: redness, irritation.<br>Unlikely to be required but if necessary treat symptomatically. |

## 5. SECTION 5: FIRE-FIGHTING MEASURES

Product is not classified as flammable, but will burn on contact with flame or exposure to high temperature (see Section 9).

- |  |  |
|--|--|
| <b>5.1 Extinguishing Media</b>                                   |  |
| Suitable Extinguishing Media                                     | Water spray, foam, dry powder or CO <sub>2</sub> .   |
| Unsuitable Extinguishing Media                                   | Do not use water jet.  |
| <b>5.2 Special hazards arising from the substance or mixture</b> | This product may give rise to hazardous fumes in a fire. Hazardous Decomposition Product(s): carbon monoxide, carbon dioxide, styrene, aliphatic hydrocarbons, traces of hydrogen bromide and bromine can be produced.   |
| <b>5.3 Advice for fire-fighters</b>                              | Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Chemical protection suit. Keep containers cool by spraying with water if exposed to fire. Flammable concentrations of pentane may accumulate on storage in closed containers. |

## 6. SECTION 6: ACCIDENTAL RELEASE MEASURES

- |  |   |
|--|---|
| <b>6.1 Personal precautions, protective equipment and emergency procedures</b> | Caution - spillages may be slippery.<br>Pentane can form explosive mixture with air. The pentane vapour is heavier than air; beware of pits and confined spaces. Remove or make safe all sources of ignition. Avoid friction, sparks, or other means of ignition. Take precautionary measures against static discharges. Use only non-sparking tools. |
| <b>6.2 Environmental precautions</b>   | Prevent entry into drains.  |
| <b>6.3 Methods and material for containment and cleaning up</b>                | If safe to do so:<br>Small spillages: Sweep up and shovel into waste drums or plastic bags. Transfer to a lidded container for disposal or recovery.<br>Large spillages: Use vacuum equipment suitable for use in hazardous locations for collecting spilt materials, where practicable. Transfer to a lidded container for disposal or recovery.     |
| <b>6.4 Reference to other sections</b>   | See Also Section 8 and 13.  |

## 7. SECTION 7: HANDLING AND STORAGE

- |  |   |
|--|---|
| <b>7.1 Precautions for safe handling</b> | Provide adequate ventilation, including appropriate local extraction. Do not breathe fumes/vapour. Avoid generation of dust clouds. Should be kept away from naked flames and other sources of ignition. Extinguish any other fire. Remove or make safe all sources of ignition. Avoid friction, sparks, or other means of ignition. The electrical system should be spark-free. When using do not smoke. Take precautionary measures against static discharges. Ensure adequate earthing. Avoid release to the environment. Permission must be obtained from the appropriate Local Authority |
|--|---|

### Process Hazards

before disposing of waste material.

Take precautionary measures against static discharges.

To avoid the build-up of static electric charge, and also the formation of an explosive pentane-air mixture, containers should be fully emptied when processing. Line velocity should not exceed 8 m/s during normal pumping operations. All parts of the plant and equipment should be electrically bonded together and connected to earth. Electrical continuity should be checked at regular intervals. Antistatic clothing and footwear should be used.

### 7.2 Conditions for safe storage, including any incompatibilities

Flammable concentrations of pentane may accumulate on storage in closed containers. Before unloading freight containers, keep doors open and ventilate for one hour.

Keep container tightly closed, in a cool, well ventilated place.

Keep away from direct sunlight and other sources of heat or ignition. Keep away from rain and moist conditions.

Bulk: Keep under inert gas.

Open top tanks should be covered with an open rigid grid.

Take precautionary measures against static discharges. The electrical system should be spark-free. The product is usually supplied in fibreboard octabins. It is recommended not to double stack octabins.

Specific design for storage rooms or vessels

Storage rooms should be kept cool to reduce pentane release, and provided with a suitable ventilation system to prevent accumulation of pentane. In addition, safety devices to alert any build up of pentane/air explosive mixtures should be used.

The electrical system should be spark-free.

Equipment to be installed in potentially explosive atmospheres should conform to the requirements of ATEX Directive 94/9/EC.

Storage Temperature

Ambient.

Storage Life

Stable under normal conditions.

Incompatible materials

Avoid storing or handling in conjunction with UN Class 1 explosives.

Suitable containers:

Steel (drums).

### 7.3 Specific end use(s)

Used primarily for the manufacture of foamed thermal insulation and packaging.

## 8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters




#### 8.1.1 Occupational Exposure Limits

The following are limits for the expanding agent (during the conversion process (expansion) the preparation evolves pentane).

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m <sup>3</sup> )	STEL (ppm)	STEL (mg/m <sup>3</sup> )	Note:
Pentane (mixed isomers)	109-66-0	600	1800	-	-	WEL

	78-78-4				
--	---------	--	--	--	--

WEL: Workplace Exposure Limit (UK HSE EH40)

<b>8.1.2 Biological limit value</b>		Not established.
<b>8.1.3 PNECs and DNELs</b>		Not established.
<b>8.2 Exposure controls</b>		
<b>8.2.1 Appropriate engineering controls</b>		Use only in well-ventilated areas.
<b>8.2.2 Personal protection equipment</b>		
Eye/face protection		Safety spectacles.
Skin protection (Hand protection/ Other)		Wear suitable gloves. Recommended: Impervious gloves (EN 374). Material NBR, thickness 0,50mm, impermeabel for solids (e.g. Ribiflex S NB 27 S, breakthrough >480 min.) Antistatic shoes type S1, S2 of S3 with PU sole or ESD shoes/boots.
Respiratory protection		An approved dust mask should be worn if dust is generated during handling. Type P1 (EN 143) or FFP1 (EN 149) "nose type" (e.g. GISS FFP1 839959).
Thermal hazards		Not applicable.
<b>8.2.3 Environmental Exposure Controls</b>		European Community and local provisions on Volatile Organic Substances (VOC), are to be fulfilled when they are applicable to the EPS industry.

## 9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

These properties are the most relevant.

<b>9.1 Information on basic physical and chemical properties</b>		
Form		Solid, Small spherical beads.
Colour		White.
Odour		Odourless.
Odour Threshold (ppm)		Not established.
pH (Value)		Not applicable.
Melting Point (°C)		Not available.
Boiling Point (°C)		Not available.
Flash Point (°C)		< -50°C (Pentane).
Upper Explosive Limit (UEL)		7.8% (v/v) (Pentane).
Lower Explosive Limit (LEL)		1.3% (v/v) (Pentane).
Auto Ignition Temperature (°C)		285°C (Pentane) (ASTM E-659).
Evaporation rate		Not applicable.
Flammability (solid, gas)		Non-flammable.
Explosive limit ranges		Not applicable.

Vapour Pressure (mm Hg)	Not applicable.
Vapour Density (Air=1)	2.5 (Pentane).
Density (g/ml)	1,02 – 1,05 (1020–1050 kg/m <sup>3</sup> ) @ 20°C (beads).
Bulk Density (g/ml)	0,6 (600 kg/m <sup>3</sup> ) @ 20°C.
Softening Point (°C)	70-75°C (beads expand with evolution of pentane).
Solubility (Water)	Insoluble.
Solubility (Other)	Soluble in aromatic hydrocarbons, halogenated solvents and ketones.
Partition Coefficient (n-Octanol/water)	Not available.
Decomposition Temperature (°C)	Not available.
Viscosity (mPa.s)	Not established.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
<b>9.2 Other information</b>	None.

## 10. SECTION 10: STABILITY AND REACTIVITY

<b>10.1 Reactivity</b>	Stable under normal conditions.
<b>10.2 Chemical stability</b>	Stable under normal conditions.
<b>10.3 Possibility of hazardous reactions</b>	In use, may form flammable/explosive vapour-air mixture.
<b>10.4 Conditions to avoid</b>	Keep away from heat, sources of ignition and direct sunlight.
<b>10.5 Incompatible materials</b>	Avoid storing or handling in conjunction with UN Class 1 explosives.
<b>10.6 Hazardous Decomposition Product(s)</b>	Pentane, styrene monomer, carbon monoxide, (in case of fire or during hot wire cutting). Release of pentane increases with temperature. (beads expand with evolution of pentane).

## 11. SECTION 11: TOXICOLOGICAL INFORMATION

This assessment is based on information available on similar products.

### 11.1 Information on toxicological effects

#### 11.1.1 Polymer

##### Acute toxicity

Inhalation The product can evolve pentane vapours, which at high concentrations may lead to dizziness, headache and anaesthetic effects.

Ingestion Unlikely to be hazardous if swallowed.

Skin Contact No data.

Eye Contact No data.

**Irritation** May cause irritation to skin and eyes.

**Corrosivity** No data.

**Sensitisation** No data.

**Repeated dose toxicity** No data.

**Carcinogenicity** No data.

**Mutagenicity** No data.

<b>Toxicity for reproduction</b>	No data.
<b>11.2 Other information</b>	None.

## 12. SECTION 12: ECOLOGICAL INFORMATION

This environmental hazard assessment is based on information available on similar products. This product contains substances which are classified as dangerous for the environment. However recent studies on aquatic organisms have shown that EPS-beads, while containing these substances, do not need to be classified for environmental hazard.

<b>12.1 Toxicity</b>	<p>Aquatic invertebrates: EC50 (48 h) &gt; 100 mg/l, Daphnia magna (OECD Guideline 202, part 1, static) Nominal concentration. The product has low solubility in the test medium. An eluate has been tested. No toxic effects occur within the range of solubility.</p> <p>Aquatic plants: EC50 (48 h) &gt; 100 mg/l, EC50 (72 h) &gt; 100 mg/l (growth rate), Desmodium subspicatus (OECD Guideline 202, part 1, static) Nominal concentration. The product has low solubility in the test medium. An eluate has been tested. No toxic effects occur within the range of solubility.</p>
<b>12.2 Persistence and degradability</b>	The product itself has not been tested. In accordance with the required stability the product is not readily biodegradable. The statement has been derived from the structure of the product. It can be largely eliminated from the water by abiotic processes, e.g. mechanical separation.
<b>12.3 Bioaccumulative potential</b>	The product has low potential for bioaccumulation. Bioconcentration factor (BCF) < 100.
<b>12.4 Mobility in soil</b>	The product is essentially insoluble in water. Expandable polystyrene sinks in fresh water, may float or sink in sea water.
<b>12.5 Effect on Effluent Treatment</b>	Practically non-toxic, EC50>100mg/l, to organisms in sewage treatment plants (estimated).
<b>12.6 Results of PBT and vPvB assessment</b>	See Section: 15.1.1.
<b>12.7 Other adverse effects</b>	Pentane has very low Global Warming Potential (< 0.00044) and zero Ozone Depletion Potential.

## 13. SECTION 13: DISPOSAL CONSIDERATIONS

Surplus, unused, old beads may still contain residual pentane. Therefore product has to be treated using all the safety measures in place for the fresh material. See Also Section 7.

<b>13.1 Waste treatment methods</b>	Recover or recycle if possible. Remove all packaging for recovery or disposal. Normal disposal is via incineration operated by an accredited disposal contractor.
<b>13.2 Additional Information</b>	Dispose of contents in accordance with local, state or national legislation.

### 14. SECTION 14: TRANSPORT INFORMATION

<b>14.1 UN number</b>	UN2211
<b>14.2 Proper Shipping Name</b>	POLYMERIC BEADS, EXPANDABLE, evolving flammable vapour (PENTANE).
<b>14.3 Transport hazard class(es)</b>	9.
<b>14.4 Packing Group</b>	III.
<b>14.5 Environmental hazards</b>	None. Not classified as a Marine Pollutant.
<b>14.6 Special precautions for user</b>	633: Keep away from any source of ignition.  Transport or conveyance within the manufacturing premises: Refer to the internal procedures and information provided by this document. Transport or conveyance outside the manufacturing premises: Apply the requirements of the regulations on transport of dangerous goods and the manufacturer's recommendation on safe loading, transporting, unloading of the material.
<b>14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable
<b>14.8 Additional Information</b>	Hazard Identification Number: 90. Tunnel Restriction Code: D/E. IMDG EMS F-A, S-I.

**Hazard label(s)**

Sea transport (IMDG)

Air transport (ICAO/IATA)



UN Class 9 miscellaneous hazard label.

### 15. SECTION 15: REGULATORY INFORMATION

<b>15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture</b>	
<b>15.1.1 EU regulations</b>	
Authorisations and/or restrictions on use	None
<b>15.1.2 National regulations</b>	Not applicable.
<b>15.2 Chemical Safety Assessment</b>	Not available.

### 16. SECTION 16: OTHER INFORMATION

This Safety Data Sheet was prepared in accordance with EC Regulation (EC) 1907/2006 (REACH), 1272/2008 (CLP) & 453/2010.

**Version 1.1 has passed over to be consistent with the msds in other languages.**

**The following sections are revised or contain new content: 1.4 , 2.2.2 and 8.2.2, 2.1, 2.2, 3 and 8.2 in version 1.4a**

**LEGEND**

LTEL	Long Term Exposure Limit.
STEL	Short Term Exposure Limit.



STOT	Specific Target Organ Toxicity.
DNEL	Derived No Effect Level.
PNEC	Predicted No Effect Concentration.
PBT	PBT: Persistent, Bioaccumulative and Toxic.
Flam. Liq. 1	Flammable liquid Category 1.
Asp. Tox. 1	Aspiration hazard Category 1.
STOT SE 3	Specific target organ toxicity — single exposure Category 3.
Aquatic Chronic 2	Hazardous to the aquatic environment Chronic Category 2.

**Regulation (EC) No. 1272/2008 (CLP).****Hazard statement(s) and Precautionary statement(s)**

H224	Extremely flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH018	In use may form flammable/explosive vapour-air mixture.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Hazard pictogram(s)**

GHS02



GHS08



GHS07



GHS09

**Training advice:**

Suitable information on safety in handling, storage and conversion of the product should be given to employees based on all the existing information. A DVD on EPS Fire Safety is available from Plastics Europe in 18 European languages. Please contact your EPS beads supplier for a copy.

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Unipol Holland gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Unipol Holland accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

**Annex to the extended Safety Data Sheet (eSDS)**

No information available.