

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 453/2010

1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier	
Product Name	UNIPOL R-EPS
Chemical Name	Regular- Expandable Polystyrene.
Synonyms	Expandable Polystyrene (containing pentane as expanding agent).
Trade name	Regular-EPS, Expandable polystyrene, poly(phenylethene).
CAS No.	UNIPOL R-EPS
EINECS No.	None assigned.
REACH Registration No.	None assigned.
1.2 Relevant identified uses of the substance or mixture and uses advised against	
Identified use(s)	Used primarily for the manufacture of foamed thermal insulation.
Uses advised against	None known.
1.3 Details of the supplier of the Safety Data Sheet	
1.3.1 EU Representative	
	Unipol Holland BV
	Postbox 824
	5340 AV Oss
	Netherlands
Telephone	+ 31 412 643 243
E-mail	algemeen@unipol.nl
E-mail (competent person)	a.janssen@unipol.nl
Technical contact:	algemeen@unipol.nl
1.4 Emergency telephone number	
Emergency Phone No.	+ 31 412 643 243
Dutch National Poison Information Centre:	+ 31 (0)30 - 274 88 88 (only for professional emergency aid personell, in case of calamities)

2. SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture	
2.1.2 Regulation (EC) No. 1272/2008 (CLP)	-
2.2 Label elements	
2.2.2 Label elements	According to Regulation (EC) No. 1272/2008 (CLP).
Product Name	Unipol R-EPS
Hazard Pictogram	None.
Signal word(s)	None.
Hazard statement(s)	EUH018: In use may form flammable/explosive vapour-air

Precautionary statement(s)	<p>mixture.</p> <p>EUH210: Safety data sheet available on request.</p> <p>P210: Keep away from heat, sparks, open flame, hot surfaces - No smoking.</p> <p>P233: Keep container tightly closed.</p> <p>P243: Take precautionary measures against static discharge.</p> <p>P403 + P235: Store in a well-ventilated place. Keep cool.</p> <p>Product releases pentane, a flammable hydrocarbon.</p> <p>May cause irritation to skin and eyes.</p>
2.3 Other hazards	
2.4 Additional Information	For full text of H/P phrases see section 16.

3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Polystyrene (CAS No. 9003-53-6), containing pentane isomers as blowing agent.

3.1 Polymer

EC Classification No. 1272/2008

Hazardous ingredient(s)	%W/W	CAS No.	EC No.	REACH Registration No.	Hazard pictogram(s) and Hazard statement(s)
Pentane (mixed isomers)	<7	109-66-0 78-78-4	203-692-4 201-142-8	01-2119459286-30 01-2119475602-38	GHS02, Flam. Liq. 1; H224, GHS08, Asp. Tox. 1; H304, GHS07, STOT SE 3; H336, GHS09, Aquatic Chronic 2; H411, EUH066.

For full text of H/P phrases see section 16.

3.2 Additional Information

See Section: 15.1.1.

4. SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures

Inhalation	Remove persons affected by vapour to fresh air. If symptoms persist, obtain medical attention.
Skin Contact	Wash skin with soap and water. If symptoms persist, obtain medical attention.
Eye Contact	Irrigate with eyewash solution or clean water, holding the eyelids apart, for at least 15 minutes. If symptoms persist, obtain medical attention.
Ingestion	Unlikely to be hazardous if swallowed. IF SWALLOWED: Do not induce vomiting. Obtain medical attention immediately if ingested.
4.2 Most important symptoms and effects, both acute and delayed	Inhalation: headache, dizziness. Eyes and skin contact: redness, irritation.

4.3 Indication of immediate medical attention and special treatment needed

Unlikely to be required but if necessary treat symptomatically.

5. SECTION 5: FIRE-FIGHTING MEASURES

Product is not classified as flammable, but will burn on contact with flame or exposure to high temperature (see Section 9).

5.1 Extinguishing Media

Suitable Extinguishing Media

Water spray, foam, dry powder or CO2.

Unsuitable Extinguishing Media

Do not use water jet.

5.2 Special hazards arising from the substance or mixture

This product may give rise to hazardous fumes in a fire. Hazardous Decomposition Product(s): carbon monoxide, carbon dioxide, styrene and aliphatic hydrocarbons can be produced.

5.3 Advice for fire-fighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Chemical protection suit. Keep containers cool by spraying with water if exposed to fire. Flammable concentrations of pentane may accumulate on storage in closed containers.

6. SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Caution - spillages may be slippery. Pentane can form explosive mixture with air. The pentane vapour is heavier than air; beware of pits and confined spaces. Remove or make safe all sources of ignition. Avoid friction, sparks, or other means of ignition. Take precautionary measures against static discharges. Use only non-sparking tools.

6.2 Environmental precautions

Prevent entry into drains.

6.3 Methods and material for containment and cleaning up

If safe to do so:
Small spillages: Sweep up and shovel into waste drums or plastic bags. Transfer to a lidded container for disposal or recovery.
Large spillages: Use vacuum equipment suitable for use in hazardous locations for collecting spilt materials, where practicable. Transfer to a lidded container for disposal or recovery.

6.4 Reference to other sections

See Also Section 8 and 13.

7. SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Provide adequate ventilation, including appropriate local extraction. Do not breathe fumes/vapour. Avoid generation of dust clouds. Should be kept away from naked flames and other sources of ignition. Extinguish any other fire. Remove or make safe all sources of ignition. Avoid friction, sparks, or other means of ignition. The electrical system should be spark-free. When using do not smoke. Take precautionary measures against static discharges. Ensure adequate earthing. Avoid release to the environment. Permission must be obtained from the appropriate Local Authority before disposing of waste material.

Process Hazards

Take precautionary measures against static discharges.

7.2 Conditions for safe storage, including any incompatibilities

Specific design for storage rooms or vessels

Storage Temperature

Storage Life

Incompatible materials

Suitable containers:

7.3 Specific end use(s)

To avoid the build-up of static electric charge, and also the formation of an explosive pentane-air mixture, containers should be fully emptied when processing. Line velocity should not exceed 8 m/s during normal pumping operations. All parts of the plant and equipment should be electrically bonded together and connected to earth. Electrical continuity should be checked at regular intervals. Antistatic clothing and footwear should be used.

Flammable concentrations of pentane may accumulate on storage in closed containers. Before unloading freight containers, keep doors open and ventilate for one hour.

Keep container tightly closed, in a cool, well ventilated place.

Keep away from direct sunlight and other sources of heat or ignition. Keep away from rain and moist conditions.

Bulk: Keep under inert gas.

Open top tanks should be covered with an open rigid grid.

Take precautionary measures against static discharges.

The electrical system should be spark-free. The product is usually supplied in fibreboard octabins. It is recommended not to double stack octabins.

Storage rooms should be kept cool to reduce pentane release, and provided with a suitable ventilation system to prevent accumulation of pentane. In addition, safety devices to alert any build up of pentane/air explosive mixtures should be used.

The electrical system should be spark-free.

Equipment to be installed in potentially explosive atmospheres should conform to the requirements of ATEX Directive 94/9/EC.

Ambient.

Stable under normal conditions.

Avoid storing or handling in conjunction with UN Class 1 explosives.

Steel (drums).

Used primarily for the manufacture of foamed thermal insulation and packaging.

8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION




8.1 Control parameters

8.1.1 Occupational Exposure Limits

The following are limits for the expanding agent, (during the conversion process (expansion) the preparation evolves pentane).

SUBSTANCE	CAS No.	LEL (8 hr TWA ppm)	LEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note:
Pentane (mixed isomers)	109-66-0 78-78-4	600	1800	-	-	WEL

WEL: Workplace Exposure Limit (UK HSE EH40)

8.1.2 Biological limit value	Not established.
8.1.3 PNECs and DNELs	Not established.
8.2 Exposure controls	
8.2.1 Appropriate engineering controls	Use only in well-ventilated areas.
8.2.2 Personal protection equipment	
Eye/face protection	Safety spectacles.
	
Skin protection (Hand protection/ Other)	Wear suitable gloves. Recommended: Impervious gloves (EN 374). Material NBR, thickness 0,50mm, impermeable for solids (e.g. Ribiflex S NB 27 S, breakthrough >480 min.) Antistatic shoes type S1, S2 of S3 with PU sole or ESD shoes/boots.
	
Respiratory protection	An approved dust mask should be worn if dust is generated during handling. Type P1 (EN 143) or FFP1 (EN 149) "nose type" (e.g. GISS FFP1 839959).
	
Thermal hazards	Not applicable.
8.2.3 Environmental Exposure Controls	European Community and local provisions on Volatile Organic Substances (VOC), are to be fulfilled when they are applicable to the EPS industry.

9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

These properties are the most relevant.

9.1 Information on basic physical and chemical properties	
Form	Solid, Small spherical beads.
Colour	White.
Odour	Odourless.
Odour Threshold (ppm)	Not established.
pH (Value)	Not applicable.
Melting Point (°C)	Not available.
Boiling Point (°C)	Not available.
Flash Point (°C)	< -50°C (Pentane).
Upper Explosive Limit (UEL)	7.8% (v/v) (Pentane).
Lower Explosive Limit (LEL)	1.3% (v/v) (Pentane).
Auto Ignition Temperature (°C)	285°C (Pentane) (ASTM E-659).
Evaporation rate	Not applicable.
Flammability (solid, gas)	Non-flammable.
Explosive limit ranges	Not applicable.
Vapour Pressure (mm Hg)	Not applicable.
Vapour Density (Air=1)	2.5 (Pentane).

Density (g/ml)	1,02-1,05 (1020-1050 kg/m ³) @ 20°C (beads).
Bulk Density (g/ml)	circa 0,6 (600 kg/m ³) @ 20°C.
Softening Point (°C)	70-75°C (beads expand with evolution of pentane).
Solubility (Water)	Insoluble.
Solubility (Other)	Soluble in aromatic hydrocarbons, halogenated solvents and ketones.
Partition Coefficient (n-Octanol/water)	Not available.
Decomposition Temperature (°C)	Not available.
Viscosity (mPa.s)	Not established.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
9.2 Other information	None.

10. SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity	Stable under normal conditions.
10.2 Chemical stability	Stable under normal conditions.
10.3 Possibility of hazardous reactions	In use, may form flammable/explosive vapour-air mixture.
10.4 Conditions to avoid	Keep away from heat, sources of ignition and direct sunlight.
10.5 Incompatible materials	Avoid storing or handling in conjunction with UN Class 1 explosives.
10.6 Hazardous Decomposition Product(s)	Pentane, styrene monomer, carbon monoxide, (in case of fire or during hot wire cutting). Release of pentane increases with temperature. (Beads expand with evolution of pentane).

11. SECTION 11: TOXICOLOGICAL INFORMATION

This assessment is based on information available on similar products.

11.1 Information on toxicological effects

11.1.1 Polymer

Acute toxicity

Inhalation The product can evolve pentane vapours, which at high concentrations may lead to dizziness, headache and anaesthetic effects.

Ingestion Unlikely to be hazardous if swallowed.

Skin Contact No data.

Eye Contact No data.

Irritation May cause irritation to skin and eyes.

Corrosivity No data.

Sensitisation No data.

Repeated dose toxicity No data.

Carcinogenicity No data.

Mutagenicity No data.

Toxicity for reproduction No data.

11.2 Other information None.

12. SECTION 12: ECOLOGICAL INFORMATION

This environmental hazard assessment is based on information available on similar products.

This product contains substances which are classified as dangerous for the environment. However recent studies on aquatic organisms have shown that EPS-beads, while containing these substances, do not need to be classified for environmental hazard.

12.1 Toxicity

Aquatic invertebrates:

EC50 (48 h) > 100 mg/l, Daphnia magna (OECD Guideline 202, part 1, static) Nominal concentration. The product has low solubility in the test medium. An eluate has been tested. No toxic effects occur within the range of solubility.

Aquatic plants:

EC50 (48 h) > 100 mg/l, EC50 (72 h) > 100 mg/l (growth rate), Desmodemus subspicatus (OECD Guideline 202, part 1, static) Nominal concentration. The product has low solubility in the test medium. An eluate has been tested. No toxic effects occur within the range of solubility.

12.2 Persistence and degradability

The product itself has not been tested. In accordance with the required stability the product is not readily biodegradable. The statement has been derived from the structure of the product. It can be largely eliminated from the water by abiotic processes, e.g. mechanical separation.

12.3 Bioaccumulative potential

The product has low potential for bioaccumulation. Bioconcentration factor (BCF) < 100.

12.4 Mobility in soil

The product is essentially insoluble in water. Expandable polystyrene sinks in fresh water, may float or sink in sea water.

12.5 Effect on Effluent Treatment

Practically non-toxic, EC50 > 100 mg/l, to organisms in sewage treatment plants (estimated).

12.6 Results of PBT and vPvB assessment

See Section: 15.1.1.

12.7 Other adverse effects

Pentane has very low Global Warming Potential (< 0.00044) and zero Ozone Depletion Potential.

13. SECTION 13: DISPOSAL CONSIDERATIONS

Surplus, unused, old beads may still contain residual pentane. Therefore product has to be treated using all the safety measures in place for the fresh material. See Also Section 7.

13.1 Waste treatment methods

Recover or recycle if possible. Remove all packaging for recovery or disposal. Normal disposal is via incineration operated by an accredited disposal contractor.

13.2 Additional Information

Dispose of contents in accordance with local, state or national legislation.

14. SECTION 14: TRANSPORT INFORMATION

14.1 UN number

UN2211

14.2 Proper Shipping Name

POLYMERIC BEADS, EXPANDABLE, evolving flammable vapour (PENTANE).

14.3	Transport hazard class(es)	9.
14.4	Packing Group	III.
14.5	Environmental hazards	None. Not classified as a Marine Pollutant.
14.6	Special precautions for user	633: Keep away from any source of ignition. Transport or conveyance within the manufacturing premises: Refer to the internal procedures and information provided by this document. Transport or conveyance outside the manufacturing premises: Apply the requirements of the regulations on transport of dangerous goods and the manufacturer's recommendation on safe loading, transporting, unloading of the material.
14.7	Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
14.8	Additional Information	Hazard Identification Number: 90. Tunnel Restriction Code: D/E. IMDG EMS F-A, S-I.

Hazard label(s)

Sea transport (IMDG)

Air transport (ICAO/IATA)



UN Class 9 miscellaneous hazard label.

15. SECTION 15: REGULATORY INFORMATION

15.1	Safety, health and environmental regulations/legislation specific for the substance or mixture	
15.1.1	EU regulations	
	Authorisations and/or restrictions on use	None.
15.1.2	National regulations	Not applicable.
15.2	Chemical Safety Assessment	Not available.

16. SECTION 16: OTHER INFORMATION

This Safety Data Sheet was prepared in accordance with EC Regulation (EC) 1907/2006 (REACH), 1272/2008 (CLP) & 453/2010.

Version 1.1 has passed over to be consistent with the msds in other languages.

The following sections contain revisions or new statements: 1.4 , 2.2.2, 2.1, 2.2, 3, 8.2 and 8.2.2in Versie 1.4a.

LEGEND

LTEL	Long Term Exposure Limit.
STEL	Short Term Exposure Limit.
STOT	Specific Target Organ Toxicity.
DNEL	Derived No Effect Level.
PNEC	Predicted No Effect Concentration.

PBT	PBT: Persistent, Bioaccumulative and Toxic.
Flam. Liq. 1	Flammable liquid Category 1.
Asp. Tox. 1	Aspiration hazard Category 1.
STOT SE 3	Specific target organ toxicity — single exposure Category 3.
Aquatic Chronic 2	Hazardous to the aquatic environment Chronic Category 2.

Regulation (EC) No. 1272/2008 (CLP).**Hazard statement(s) and Precautionary statement(s)**

H224	Extremely flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH018	In use may form flammable/explosive vapour-air mixture.
EUH066	Repeated exposure may cause skin dryness or cracking.

Hazard pictogram(s)

GHS02



GHS08



GHS07



GHS09

Training advice:

Suitable information on safety in handling, storage and conversion of the product should be given to employees based on all the existing information. A DVD on EPS Fire Safety is available from Plastics Europe in 18 European languages. Please contact your EPS beads supplier for a copy.

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Unipol Holland gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Unipol Holland accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Annex to the extended Safety Data Sheet (eSDS)

No information available.